


UHF & BLUETOOTH® MULTI-TECHNOLOGY READER

MIXED VEHICLE & DRIVER IDENTIFICATION



BENEFITS

- Hands-free identification of the vehicle and/or the driver
- Highly adaptable and secure identification
- Visual and audio user feedback
- Interoperable and multi-protocol



- Add your logo
- Casing color options

SPECTRE nano, the most compact UHF and Bluetooth® reader on the market, improves the user experience while securing and eliminating vehicle access lines.

MULTI-TECHNOLOGY AT THE SERVICE OF INSTINCTIVE IDENTIFICATION

SPECTRE nano facilitates access control for vehicles and drivers with different profiles (visitors, employees, tenants, etc.) thanks to multiple identification technologies.

Passive UHF technology

The reader provides UHF identification up to 6 m*.

The passive credentials (without battery) require no maintenance and have an unlimited life span.

Bluetooth® Smartphones

The reader offers many identification modes - long distance, hands-free or Proximity - to make your access control both secure and instinctive!

Fully integrated into the STid Mobile ID® ecosystem, SPECTRE nano allows users to use their virtual card for both parking and pedestrian access.

Mixed identification

SPECTRE nano reads heterogeneous identifiers:

- the virtual card for smooth management of visitor and employee access,
- the UHF windshield tag for tracking vehicle fleets
- both simultaneously for vehicle and driver identification.

SECURITY CONTROLLED FROM END-TO-END

The reader benefits from the highest levels of security, guaranteeing the authenticity and confidentiality of data, using encryption methods recognized and recommended by independent organizations (ANSSI, FIPS, etc.):

- Encrypted / signed credentials to ensure anti-cloning and anti-replay protection.
- EAL5+ certified key storage.
- Self-protection function to erase security keys.
- Secure end-to-end bidirectional communication using SSCP® and Open Supervised Device Protocol (OSDP™) protocols.

EASY TO INSTALL

The reader can be configured in seconds via USB cable, UHF / virtual card, or protocol. Its VESA 75 x 75 standard compatible mounting system allows for optimal wall or pole installation regardless of the site configuration.

STANDING THE TEST OF TIME

It integrates a reinforced anti-vandal structure IK10 to resist shocks and malicious acts. IP65, it is designed for outdoor installation in harsh environments: vibration, dust, heavy rain, saline environments, etc.

APPLICATIONS

- Parking access: tertiary, administration, communities, industries...
- Shared vehicle management
- Sensitive sites
- Visitor management
- Two-wheeler identification
- Bus stations (...)

CHARACTERISTICS

Operating frequency/Standards	UHF - 2 versions: - 865 - 868 MHz : 866 MHz ETSI (Europe), Morocco (regulation n°ANRT/DG/n°7-10), etc. - 902 - 928 MHz : 915 MHz FCC Part 15 (USA), Australia, New Zealand, etc. Bluetooth®												
Chip Compatibilities	EPC1 Gen 2 / ISO18000-63 STid Mobile ID® (Bluetooth® virtual card) 4 possible configurations: UHF only, UHF or Bluetooth®, UHF then Bluetooth®, Bluetooth® then UHF												
Functions	Read only EPC (UHF) / CSN (Bluetooth®) or secure EPC encrypted / signed (UHF) / private ID (Bluetooth®) Controlled by protocol (read/write)												
Communication interfaces	- Standard TTL output: ISO2 protocol (Clock&Data) or Wiegand - RS232 with SSCP® v1 & v2 secure communication protocols - RS485 with SSCP® v1 & v2 secure communication protocols; OSDP™ v1 (plain text) and v2 (Secure Channel Protocol)												
Antenna	Integrated antenna with circular polarization												
RF power	Up to 27 dBm (adjustable power)												
Reading distances*	Up to 6 m with ETA tag and TeleTag® passive tag Up to 20 m with a Bluetooth® smartphone Adjustable reading range on each reader <i>The reading range may vary depending on the type of vehicle, the installation conditions and the local regulations allowed.</i>												
Data protection	Yes - Software protection and EAL5+ certified crypto processor for secure key storage												
Light indicator	1 LED 7 colors (green, red, blue, orange, purple, turquoise, white) Configurable by card (classic or virtual with STid Settings application), software, or controlled by external command (0V)												
Audio indicator	Integrated buzzer with adjustable intensity Configurable by card (classic or virtual with STid Settings application), software, or controlled by external command (0V) depending on interface. Can be activated / deactivated by jumper												
Input / Output (I/O)	1 input (for control by ground loop / presence detector...) - 1 output (to control traffic lights...)												
Relay	1 power relay of 24 VDC 2A (control of a barrier...)												
Power requirement	900 mA / typically 12 VDC / 1.5 A / 12 VDC max												
Power supply	From 9 VDC to 36 VDC (typically 12 VDC)												
Connectors	8-pin plug-in screw terminal block (0.1") and cable gland												
Materials	ABS and polycarbonate (ABS-PC) / Aluminum												
Dimensions (h x w x d) / Weight	185 x 230 x 35 mm / 7.2" x 9" x 1.4" / 1.25 kg / 35.3 oz												
Operating temperatures	From - 30°C to + 60°C / From - 22°F to + 140°F												
Storage temperatures	From - 40°C to + 65°C / From - 40°F to + 149°F												
Tamper function	Detection of the opening of the cover by infrared sensor and mechanical switch with possibility of erasing the keys and/or message to the controller												
Protection / Resistance	IP65 certified - Weather, water, and dust resistant / Humidity: 5 - 95% / IK10 certified vandal-proof front face structure												
Mounting	Supplied with wall mounting bracket Compliant with VESA 75 x 75 universal mounting kits (optional) - Adjustable wall-mounting kit - Pole-mounted												
Certifications	CE (Europe), FCC (USA), IC (Canada) and UL												
Part numbers x: versions = 4 - 865 - 868 MHz; 5 - 902 - 928 MHz	<table border="0"> <tr> <td>Read only - TTL</td> <td>SNA-Rx1-A/BT4-xx/1</td> </tr> <tr> <td>Secure read only - RS232</td> <td>SNA-Rx2-A/BT4-5AB/1</td> </tr> <tr> <td>Secure read only - RS485</td> <td>SNA-Rx3-A/BT4-7AB/1</td> </tr> <tr> <td>Operates using SSCP® protocol v1 & v2 - RS232</td> <td>SNA-Wx2-A/BT4-5AX/1</td> </tr> <tr> <td>Operates using OSDP® protocol v1 & v2 - RS485</td> <td>SNA-Wx3-A/BT4-7AX/1</td> </tr> <tr> <td>Operates using OSDP™ protocol v1 & v2 - RS485</td> <td>SNA-Wx3-A/BT4-7OS/1</td> </tr> </table>	Read only - TTL	SNA-Rx1-A/BT4-xx/1	Secure read only - RS232	SNA-Rx2-A/BT4-5AB/1	Secure read only - RS485	SNA-Rx3-A/BT4-7AB/1	Operates using SSCP® protocol v1 & v2 - RS232	SNA-Wx2-A/BT4-5AX/1	Operates using OSDP® protocol v1 & v2 - RS485	SNA-Wx3-A/BT4-7AX/1	Operates using OSDP™ protocol v1 & v2 - RS485	SNA-Wx3-A/BT4-7OS/1
Read only - TTL	SNA-Rx1-A/BT4-xx/1												
Secure read only - RS232	SNA-Rx2-A/BT4-5AB/1												
Secure read only - RS485	SNA-Rx3-A/BT4-7AB/1												
Operates using SSCP® protocol v1 & v2 - RS232	SNA-Wx2-A/BT4-5AX/1												
Operates using OSDP® protocol v1 & v2 - RS485	SNA-Wx3-A/BT4-7AX/1												
Operates using OSDP™ protocol v1 & v2 - RS485	SNA-Wx3-A/BT4-7OS/1												

DISCOVER OUR CREDENTIALS AND OUR ERGONOMIC MANAGEMENT TOOLS



TeleTag® & ETA
UHF windshield tags and labels



CCT & PCG
UHF or dual frequency cards and key fobs



The STid Mobile ID® application
Smartphones / Bluetooth® connected watches



ULTRYS programming kit and SSCP® and OSDP™ protocols



STid Mobile ID Online Portal
Web-based platform for remote management of your virtual cards

* Attention: information on communication distances: measured at the center of the antenna, depending on the positioning of the vehicle, the antenna configuration, the installation environment of the reader, the supply voltage, and the local regulations in effect. External disturbances can cause the reading range to decrease. The reading performance depends on the positioning of the tag and the type of windshield. Impervious windshields can affect reading performance. It is imperative to place the tag in the resist zones.

Legal Notice: STid, STid Mobile ID® and SSCP® are registered trademarks of STid SAS. All trademarks mentioned in this document belong to their respective owners. All rights reserved - This document is the sole property of STid. STid reserves the right, at any time and without notice, to make changes to this document and/or to stop marketing its products and services. The photographs are non-contractual.

Headquarters / EMEA

13850 Créasque, France
Tel.: +33 (0)4 42 12 60 60

PARIS-IDF Office

92290 Châtenay-Malabry, France
Tel.: +33 (0)1 43 50 11 43

STid UK Ltd.

Callows Hill, Warwick CV34 6UW, UK
Tel.: +44 (0) 192 621 7884

NORTH AMERICA Office

Irving, Texas 75063-2670, USA
Tel.: +1 469 524 3442

LATINO AMERICA Office

San Rafael 06470 CDMX, México
Tel.: +52 (55) 5256 4706